



## Enecsys Micro Inverters

### SMI-S240W-60



#### Maximized Energy Harvest

---

#### Improved Safety

---

#### Increased Lifetime & Reliability

---

#### Enhanced Monitoring Capability

---

#### Simplified PV Array Design & Installation

---

Enecsys develops, manufactures and markets world leading, highly reliable grid-connected solar micro inverters and monitoring systems that offer an outstanding value proposition for solar PV systems.

**Enecsys Ltd**  
Harston Mill, Royston Rd  
Cambridge, CB22 7GG, UK  
Tel. +44 1223 792101  
Fax. +44 1223 792103

**Enecsys Europe GmbH**  
Louisenstraße 65  
61348 Bad Homburg, Germany  
Tel. +49 6172 8552430  
Fax. +49 6172 8552440

**Enecsys LLC**  
275 Shoreline Drive, Suite 200  
Redwood Shores, CA 94065, USA  
Tel. +1 855-ENECYSYS  
(Toll Free in USA)  
Tel. +1 650-730-5700

**Enecsys Taiwan**  
9F, No.8, Ln. 321, Yangguang St  
Neihu District, Taipei City 114  
Taiwan (R.O.C.)  
Tel. +886-2-2627-6118

**Enecsys France**  
Tel. +33 (0)4 13 68 09 64

#### Technical Specification

SMI-S240W-60-(see "ordering information" for region code)

##### Input Data (DC)

Nominal Input Power	240W
Recommended Input Power (STC)	260W
Maximum DC Voltage	44V
Minimum DC Voltage	20V
MPPT Voltage Range	23V - 35V
Maximum Input Current	12A

##### Output Data (AC)

Maximum AC Output Power	225W
Nominal AC Output Current	0.98A
Nominal Output Voltage	230V
Nominal Frequency	50Hz
Power Factor	> 0.95
Total Harmonic Distortion	< 5%

##### Efficiency

Euro Efficiency	91.5%*1
Peak Efficiency	94.8%
Maximum Night Power Consumption	< 30mW

##### Mechanical Data

Operating Temperature Range	-40°C to 85°C
Enclosure Rating	IP66
Dimensions (LxHxW)	262mm x 160mm x 35mm*2
Weight	1.8kg
Cooling	Natural Convection

##### Features & Compliance

Safety Class Compliance	CE, pr EN 62109-1, AS/NZS 3100
EMC (Emission & Immunity) Compliance	EN61000-6-3, EN61000-6-1
Grid Connection Compliance	G83/ 1-1, VDE 0126-1, VDE 4105, IEC 61727, IEC 62116, AS 4777, RD 1699*3
Communication	Zigbee IEEE 802.15.4
Connector	MC4 compatible
PV Compatibility	Compatible with most 60 cell modules
Warranty	20 Years (at full ambient temperature range)
Technology	Thin film capacitors
Isolation	Galvanic

##### Ordering Information

Region code	Region
-AU	Australia
-ES	Spain
-DE	Germany
-FR	France
-IT	Italy
-UK	United Kingdom

\*1 - Efficiency maintained over full ambient temperature range from -40°C to 85°C and at nominal output power  
 \*2 - Without the mounting bracket  
 \*3 - In accordance with the Enecsys installation guidelines (please refer to the Enecsys Installation Manual)  
 All technical specifications contained within this document are subject to change without prior notice