

Flat plate solar collector

The SOLC201 is a high quality, efficient solar flat plate collector with a 1365Wp output, making it the collector of choice for a range of domestic and commercial installations.

The SOLC201 consists of a laser welded meander pipe with a high selective full area absorber coating and 30mm rear insulation. The whole assembly is encased in an anthracite anodised aluminium frame for a neat construction. The collectors can be connected in series in either horizontal or vertical orientation to suit the available roof space.

Compression fittings make the lightweight SOLC201 easy to install and the extensive range of accessories available for on-roof or free standing installations means the SOLC201 is suitable for a wide range of applications.

The SOLC201 collectors can be combined with a choice of either the premium SOLPU1 pump station or the new cost effective SOLPU0 module, providing an ultra cost effective solar thermal solution.

The collector is Solar Keymark approved and has the benefit of a 10 year warranty, assuring the quality and longevity of the collector.

Key Features

- Standard efficiency solar thermal collector
- Suitable for portrait or landscape orientation with connection of up to 4 panels in series
- Easy to install with Dimplex roof fixing kits:
 - Slate
 - Tile
 - Coach bolts
 - Flat roof
 - Free standing
- Lightweight – only 29kg per panel when empty
- 3.2mm clear solar safety glass with 85% transmission allowing the collector to absorb a wide range of the solar spectrum
- The clear safety glass covering has passed optional impact resistance tests as detailed in EN12975-2
- Aluminium, anthracite powder coated frame provides lightweight protection for the absorber that blends with the roof
- Spring suspended aluminium absorber sheet providing high efficiency over product life span
- Laser welded meander absorber for low pressure drop of overall collector field
- Compression fittings for ease of installation.
- Each panel has 4 connections allowing:
 - Left or right hand connections
 - Up to 4 collectors directly connected together
 - Collectors connected in parallel, thus lowering overall pressure drop of array
 - Same collector for portrait and landscape orientations
 - Individual options to position sensor pocket for maximum flexibility
- 10 year warranty
- Solar Keymark approved



Specifications

Gross collector area (m ²)	2.01
Absorber/Aperture area (m ²)	1.85
Length (mm)	1908
Width (mm)	1058
Height (mm)	75
Weight – empty (kg)	29
Liquid content (l)	1.4
Glass	3.2mm low iron solar safety glass
Heat loss coefficient	a1: 3.93 W/m ² K a2: 0.0148 W/m ² /K ²
Stagnation temperature (°C)	199
Absorber material	Aluminium
Peak power (W)	1365
Absorption	90%
Emission	5%
Connections	Compression
Transmission of glass	85%
Max operating pressure (bar)	10

Dimplex Solar Thermal System Packages

ROOF KIT PACKAGES
Choice of 2.01m ² , 4.02m ² and 6.03m ² collector kits
On roof mounting for plain tile, corrugated tile or slate roofs
In roof mounting for plain tile or slate roofs (Nov 2011)
Free standing panels for flat roofs or ground level mounting

HYDRAULIC PACKAGES
Choice of standard or premium hydraulic packs
Include pump station, controller, heat transfer fluid, expansion vessel and fixing kit

PACKAGE OPTIONS	
SOL201 – 1 panel	Add suffix to item code CT for corrugated tile PT for plain tile S for slate tile CB for coach bolt F for free standing
SOL402 – 2 panel	
SOL603 – 3 panel	

HYDRAULIC PACK OPTIONS
SOLHYPK0 – standard pack, with return only pump station
SOLHYPK1 – premium pack, with flow/return pump station



Dimplex EC-Eau Solar Cylinders

DIMPLEX EC-EAU SOLAR CYLINDERS
Unvented, stainless steel construction
Choice of models from 175 – 300 litres
Indirect (twin coil) and direct (solar coil only) options
Optimally sized, high surface area heat exchangers for solar operation
Very low standing heat losses, due to 60mm CFC-free foam insulation and innovative design features
Manufactured from sustainable and recycled materials
25 year vessel warranty
Supplied complete with expansion vessel and all necessary safety equipment
KIWA approved

INDIRECT MODELS
ECSi175ST-580 – 175l twin coil
ECSi210ST-580 – 210l twin coil
ECSi250ST-580 – 250l twin coil
ECSi300ST-580 – 300l twin coil

DIRECT MODELS
ECSd175ST-580 – 175l single coil
ECSd210ST-580 – 210l single coil
ECSd250ST-580 – 250l single coil
ECSd300ST-580 – 300l single coil

Please see our EC-Eau cylinder brochure for full technical details

